

Plank 14 mm tongue/ groove (Down Town)

Technical information:

Dimension:

500 - 1700 x 139 x 14 mm
(mixture of divided length and twin planks)

Toplayer:

about 3.5 mm

Construction:

3-layer construction; Hardwood toplayer,
bottom- and middlelayer made of spruce
Toplayer about 3.5 mm
Middlelayer 8.8 mm
Bottomlayer 1.7 mm

Boards per carton/ sqm:

10/ 3.06

Cartons per palett/ sqm:

42/ 128.52

**Weight per
carton/ palett in kg:**

24/ 1008.0

Fire behavior ¹⁾:

Dfl-s1

Content of formaldehyd ¹⁾:

E1

**Content of
pentachlorophenol (PCP) ¹⁾:**

beyond what can be proved

Density kg/m³ ¹⁾:

approx. 550

Antislip performance:

Protect-Ultra	USRV 11 ¹⁾	Protect-Ultra	R9 ²⁾
Ecoline	USRV 24 ¹⁾	Ecoline	R10 ²⁾
Matt lacquer	USRV 26 ¹⁾		

Abrasion resistance:

Protect-Ultra	70/ 1100 ³⁾	Protect-Ultra	100 ⁴⁾
---------------	------------------------	---------------	-------------------

Thermal conductivity ¹⁾:

0.15 W/mK

Areal thermal resistance ⁵⁾:

0.10 m²/mK



Plank 14 mm tongue/ groove (Down Town)



¹⁾ according to DIN EN 14342, ²⁾ according to DIN 51130, ³⁾ according to ENV 13696, ⁴⁾ according to DIN 68861, ⁵⁾ according to EN 12524